

FABRICATED HOUSING ORDER FORM

PART NUMBER

FABRICATED 9"-10" REAR END HOUSING ORDER FORM All of the following information is required to build your rear end housing. A completed order form must accompany this spec sheet. No work will begin on the rear end housing until payment has been made. WHEELIE BAR TOP MOUNTS: ☐Yes ☐ No Housing and Bracket Options HOUSING TYPE: ☐ Pro Mod What is the desired center to center width of the wheelie bar top ☐ Pro Series ☐ QM Series What is the desired I.D. width of the mounting wheelie bar top mounts?_ HOUSING MATERIAL: (QM SERIES ONLY) ☐ Mild Steel □ 4130 ANTI-ROLL BAR MOUNTS: ☐ Yes ☐ No ☐ Centered Std on Pro Series HOUSING BRACKETS: ☐ Offset QM Series only 4-LINK: ☐ Quarter-Max 4-LINK STRAP: ☐ Yes ☐ No ☐ Quarter-Max w/ Adj. Shock Mnt. ☐ Pro Series Std on QM & Pro Series LOWER SUPPORT: ☐ Yes ☐ No Std on Pro Series ☐ Pro Series Brackets w/ Adj. Shock Mnt. MACHINE HOUSING FACE: ☐ Yes ☐ No ☐ Extreme Pro Series FLOATER: (Strange Only) ☐ Yes ☐ No (Choice of bolt pattern) ☐ Extreme Pro Series w/ Adj. Shock Mnt. ☐ QM Pro Billet (Pro Mod Housing Only Measurements and Component Details □ Other Diagram Measurements: AVAILABLE BRACKET WIDTHS FOR PRO SERIES STARTING AT 16" Std on Axle Flange to Axle Flange (Without Brake Hats)____ Pro Series Housing End to End_ AVAILABLE BRACKET WIDTHS FOR QM SERIES STARTING AT 18-1/4" Std on Bracket Center to Center___ **OM Series** Axle Offset_ **HOUSING END & OFFSET:** LADDER BAR: □ 180° ☐ 180° w/ Adj. Shock Holes FLOATER HOUSING ONLY ☐ 360° w/Threaded Shock Mnts. End of spindle to end of spindle width_ OR DOUBLER PLATES: (Pro Series or Extreme Pro Series Only) Wheel to Wheel width_ □ Yes □ No ☐ Strange 2-pc 2.351" (L55005BB) ☐ Big Ford (early) 1/2" bolts 2.332" (H1135) Additional Mounts and Specifications VENT: ☐ Yes ☐ No Std on Pro Series ☐ Big Ford (late) 3/8" bolts 2.500" (H1137) PINION: ☐ Center ☐ Offset QM Series only Std on Pro Series ☐ Olds (sym.) 2.832" (H1132) How Much Offset? QM Series only BACK BRACE: ☐ Yes ☐ No Std on Pro Series ☐ Double Row 2.832" (H1136) Axle Flange to Axle Flange (Without Brake Hats):___ Are your shocks mounted 90° vertically for brace clearance? ☐ Yes ☐ No What is the width center to center of your shock mounts? Housing End to End: ___ Bracket Center to Center: ___ WISHBONE MOUNTS: Yes No □ 5/8" Rod End Axle Offset: □ 3/4" Rod End What is the I.D. width of the wishbone mounting tabs?_ BRAND OF AXLES: _____ ROD END SIZE: _____ BRAND OF BRAKES: HAT THICKNESS:

Customer Agreement: This form must be signed by the customer before the order is processed. By signing below I confirm that I accept responsibility for the accuracy of the information provided on this order and agree to the policies of Quarter-Max Racing. I understand that these parts will be ordered and manufactured to the specifications that I have provided on this form. I acknowledge that I have verified that all of the information is correct. I confirm that Quarter-Max Racing. will not be liable in the event that I have made an error on this form. I further acknowledge that I will be responsible for any and all costs that are related to this order, and any modifications that may be necessary to correct any errors made on my behalf.

SIGN:	PRINT:	DATE:	- 1	- 1	